



CF MESA & LIGHT MESA WALL PANEL

The Metl-Span III CF Mesa and Light Mesa wall panels are well suited for exterior and interior partition wall applications. The lightly corrugated profile on both faces of the panel ensures symmetry from outside of the building to inside, and from room to room in partition installations. The CF Mesa and Light Mesa wall panels may be used for exterior wall applications, but they are not recommended for use on exterior walls of low temperature buildings.

EXTERIOR COLORS

Eight standard colors in full strength fluoropolymer PVF²:

- Polar White
- Regal Gray
- Aegean Blue
- Sandstone
- Desert Beige
- Sculpture Bronze*
- Forest Green*
- Brick Red*

*Sculpture Bronze, Brick Red and Forest Green are not recommended for exterior color on cooler and freezer buildings.

A new expanded palette of premium colors is also available for non-cold storage buildings.

NOTE: Prices may vary by color, gauge and quantity of metal. Interior color and coating is USDA compliant Igloo White polyester.

CF MESA & LIGHT MESA WALL PANEL FEATURES

Exterior Profile: Mesa Wave pattern, 1/8" deep

Light Mesa Wave pattern, 1/16" deep

Interior Profile: Mesa Wave pattern, 1/8" deep

Light Mesa Wave pattern, 1/16" deep

Foam Core: Foamed-in-place, Blister-Free, Non-CFC polyurethane, Factory Mutual Class I approval

Module Widths: 30", 36", 42" for Mesa and Light Mesa Profiles

Panel Thickness: Mesa Profile - 2", 2-1/2", 3", 4", 5", 6"

Light Mesa Profile - 2", 2-1/2", 3", 4"

Panel Lengths: 8'-0" to 53'-0"

Exterior Facings: Stucco embossed galvanized and/or aluminum-zinc coated steel in 26 ga., 24 ga. and 22 ga.

Interior Facings: Stucco embossed galvanized and/or aluminum-zinc coated steel in 26 ga., 24 ga. and 22 ga. Type 304 stainless steel in 26 ga. unpainted

Finishes: Full strength fluoropolymer PVF² and siliconized polyester

Joint: Offset double tongue and groove with extended metal shelf for positive face fastening

Fastening: Wafer head fastener and clip concealed in the side joint

1497 N. Kealy, Lewisville, Texas 75057
877.585.9969 • FAX: 972.420.9382 • EMAIL: panel@metlspan.com

WWW.METLSPAN.COM

