

TUFF-WALL® INSULATED WALL PANEL

Metl-Span's new Tuff-Wall® is an exceptionally attractive stucco-like insulated wall panel that provides the masonry look that many designers and communities desire. The exterior stucco-like surface of the panel is a hard aggregated fiber reinforced polymer coating

created with the factory applied Tuff-Cote™ finish system. Tuff-Cote™ finish offers an extremely durable; impact and abrasion resistant coating that withstands severe weather conditions.

Unlike field-applied finishes that are vulnerable to damp or cold weather during installation, Tuff-Wall® panels can be erected in virtually any weather condition. The interior face of the Tuff-Wall® panel is finished with an attractive Mesa profile and painted with a white polyester coating. As an added value, Tuff-Wall® panels function as the finished interior walls in many applications.



- The masonry look of stucco with the efficiency of an insulated metal panel.
- The field-tested and proven Tuff-Cote™ technology
- A durable finish that is highly resistant to impact and abrasion
- A 10-year limited warranty

MODULE WIDTH: 36", 42"

PANEL THICKNESS: 2", 2-1/2", 3", 4"

"R"-VALUE (NOMINAL): 2", R-16; 2-1/2", R-20;

3", R-24; 4", R-32

PANEL LENGTHS: 8'-0" to 40'-0"

EXTERIOR FACE: Non-profiled, stucco embossed G-90 galvanized steel: 26 Ga., 24 Ga. and 22 Ga. with

factory applied Tuff-Cote™ finish system.

EXTERIOR TEXTURE: Tuff-Cote[™] finish system - a hard aggregated fiber reinforced polymer coating.

INTERIOR FACE: Stucco embossed G-90 galvanized steel: 26 Ga., 24 Ga. and 22 Ga., Type 304 stainless steel in 26 Ga. unpainted.

PANEL JOINT: Offset double tongue and groove with extended metal shelf for positive face fastening.



MEDIUM BEIGE

LIGHT STONE

1497 N. Kealy, Lewisville, Texas 75057 877.585.9969 • FAX: 972.436.0648 • EMAIL: panel@metl-span.com



