



CF STRIATED WALL PANEL

The Metl-Span III CF Striated wall panel is an attractive and economical alternative to typical flat wall panels. The exterior face is lightly profiled with narrow longitudinal striations to 1/32" depth and exhibits a virtual flat appearance from a short distance away. The CF Striated wall panel is an exceptional value combining the aesthetics of a flat wall panel and high insulation ratings of a Blister-Free polyurethane core.

EXTERIOR COLORS

Eight standard colors in full strength fluoropolymer PVF²:

- Polar White
- Regal Gray
- Aegean Blue
- Sandstone
- Desert Beige
- Sculpture Bronze*
- Forest Green*
- Brick Red*

*Sculpture Bronze, Brick Red and Forest Green are not recommended for exterior color on cooler and freezer buildings.

A new expanded palette of premium colors is also available for non-cold storage buildings.

NOTE: Prices may vary by color, gauge and quantity of metal. Interior color and coating is USDA compliant Igloo White polyester.

CF STRIATED WALL PANEL FEATURES

Exterior Profile: Longitudinal Striations, 1/32" deep

Interior Profile: Mesa Wave pattern, 1/8" deep

Foam Core: Foamed-in-place, Blister-Free, Non-CFC polyurethane, Factory Mutual Class I approval

Module Widths: 30", 36", 42"

Panel Thickness: 2", 2-1/2", 3", 4"

Panel Lengths: 8'-0" to 40'-0" for the 30" and 36" widths, 8'-0" to 32'-0" for the 42" width

Exterior Facings: Stucco embossed galvanized and/or aluminum-zinc coated steel in 26 ga., 24 ga. and 22 ga. (Note: 26 ga. is not available on the exterior face of the 42" wide Striated panel.)

Interior Facings: Stucco embossed galvanized and/or aluminum-zinc coated steel in 26 ga., 24 ga. and 22 ga. Type 304 stainless steel in 26 ga. unpainted

Finishes: Full strength fluoropolymer PVF² and siliconized polyester

Joint: Offset double tongue and groove with extended metal shelf for positive face fastening

Fastening: Wafer head fastener and clip concealed in the side joint

CF STRIATED WALL PANEL METL-SPAN III POLYURETHANE INSULATED PANELS

1497 N. Kealy, Lewisville, Texas 75057

877.585.9969 • FAX: 972.420.9382 • EMAIL: panel@metlspan.com

WWW.METLSPAN.COM

